

Rotary Tillers, Reverse Tine Rotation

RTR10 Series			
	RTR1042	RTR1050	RTR1058
Width	42"	50"	58"
Overall Width	47 5/16"	55 5/16"	63 5/16"
Weight	403#	430#	474#
Number of flanges	5	6	7
Number of Tines per Flange	4	4	4
Driveline	Category II Shear bolt - standard Slip Clutch - optional		
Gearbox	25 HP input at 540rpm 1.92:1 ratio Cast iron housing, straight bevel gears		
Gearbox Lubrication	SAE 90 oil		
Drive Chain	#80 roller chain in flowable grease bath		
Drive Chain Lubrication	Shell Alvania EP 00 or equivalent		
Sprockets	Case hardened teeth, splined bores		
Rotor Swing Diameter	15"		
Rotor Shaft Speed	225 rpm at 540 rpm PTO		
Recommended Maximum PTO HP	25 HP		
Hitch Type	Category I, offsetable, works with Land Pride Quick-Hitch (Note: Cannot be offset when using the Quick-Hitch)		

Designs, specifications, features and information are subject to change without notice.

Rotary Tillers, Reverse Tine Rotation

RTR15 Series		
Model	RTR1550	RTR1558
Width	50"	58"
Overall Width	56 1/4"	64 1/4"
Weight	455#	489#
Number of Flanges	6	7
Number of Tines per Flange	4	4
Driveline	Category III Heavy Duty Shear bolt - standard Slip Clutch - optional	
Gearbox	35 HP input at 540 rpm 1.92:1 ratio Cast iron housing, straight bevel gears	
Gearbox Lubrication	SAE 80-90W EP oil	
Drive Chain	#80 roller chain in flowable grease bath	
Drive Chain Lubrication	Shell Alvania EP 00 or equivalent	
Sprockets	Case hardened teeth, splined bores	
Rotor Swing Diameter	15"	
Rotor Shaft Speed	211 rpm at 540 rpm PTO	
Recommended Maximum PTO HP	35 HP	
Hitch Type	Category I, Sideshift capabilities, works with Land Pride Quick-Hitch (Note: Sideshift capability also works with Land Pride Quick-Hitch)	

Designs, specifications, features and information are subject to change without notice.